

CONNECT THESE 3 FOR EXCELLENCE





CURV 500®
Portable Array System
Entertainer Set

The CURV 500® is an innovative system, uniquely combining portability, sound perfection and ease of use. The system comprises 3 components that can be connected with ease.

It is based around the SmartLink® adapter. Up to four Array Satellites can be effortlessly interconnected with the LD Systems-patented click mechanism delivering plug-and-play convenience. The adapter also provides the connection to the subwoofer, which serves as a control unit for the entire system, acting both as traditional bass box and mixing desk.

2 | CURV® 500

GUESS WHY IT'S CALLED "SMARTLINK®"?

The innovative SmartLink® adapter forms the basis of the system. On top of that up to four Array Satellites can be effortlessly interconnected with the LD Systems-patented click mechanism: simply press the connection button, join the two modules by their guide rails and release the button to engage.

Easy-Click? Plug-and-Play? Whatever. Connected in 2 seconds is what counts. That's at least what our engineers thought. The mechanical connection also provides signal transmission: no other cables are needed.



SIZE: XS **SOUND: XL!**

The speaker columns are equipped with up to four modular array satellites arranged in a curve. The result is extremely clear, three-dimensional sound – similar to the sound generated by large line arrays.



Even a single 12 x 12 cm array satellite produces excellent sound results. This is guaranteed by LD Systems' in-house developed WaveAhead® technology, whereby three tweeters are arranged vertically in front of a high power fullrange driver, perfectly blending and dispersing the sound.



Actual Size



La. Singer-songwriters, jazz musicians, entertainers, speakers: everyone loves technology that fits into any trunk, is simply to assemble and produces the very best results. Like the new CURV 500®.

The integrated 4-channel mixing desk provides connectivity for microphones, instruments and laptops. Its built-in Bluetooth® technology permits wireless data transmission from smartphones or tablets and digital sound effects can also be generated via the 24-bit processor.

DESIGNED TO MAKE YOUR LIFE EASIER.

Subwoofer with integrated 4-Channel Mixer Outputs

2 x Array Satellite Out

Line Out (XLR)

Inputs 1x Mic/Hi-Z

(XLR/6,3mm Jack Combo) (Speakon compatible) (XLR/6,3mm Jack Combo) System Out (5-pin XLR)

2x Line (XLR/6,3mm Jack Combo) 3.5 mm Jack

Features

DFX (Ch1-2) DFX Presets DSP Presets Bluetooth® Link 👔 Mono/Stereo Sub Level Main Level



back view



top view

10 I CURV® 500

POWER TO THE PEOPLE.

The CURV 500® is an all-rounder — for music and for speaking. It provides a big live music sound, is a DJ's high-performance powerhouse and delivers clear spoken words and lectures. Thanks to its versatility, it is also ideal for use on exhibition stands, in clubs and smaller spaces. It represents an ideal, ultra-portable unit for stand-alone entertainers, bands and speakers and always delivers the right sound. One way or another: the audience listens. With pleasure.




playing: in bars, clubs, studios and even as a home entertainment system. It can be permanently installed with versatile wall and ceiling bracket systems wherever perfect sound quality is called for. This is where the benefits of the compact CURV 500® come into their own. (CURV 500®AVS also available in white!)

One system – several options. The CURV 500® can be installed on the wall or ceiling, depending on the configuration of the space.


Up to 4 Array Satellites can be combined, in ascending or descending order, using the discreet fixing modules and the phoenix connectors on the rear

side of the SmartLink® adapter. Whatever works best!

GREAT SOUND CAN BE INSTALLED.



CURV 500 CMB Ceilingmount




CURV 500 WMB /W
Wallmount downward



Wallmounted upward


The brackets can be fixed to the wall or ceiling. Wall-mounted, the line array can be assembled from the floor up or even suspended.



CURV 500 ISUB 10" Installation subwoofer

CURV 500 TMB

Clamp for Truss



CURV 500 IAMP4-Channel installation amplifier

14 | CURV® 500 | 15 | C

BIG TECHNOLOGY:COMPACT DIMENSIONS



LD Systems' WaveAhead® technology places a vertical tweeter array in front of a high-performance full range transducer. This proprietary design reduces reflections from ceilings and floors resulting in clear, consistent coverage.

The tightly packed tweeter array allows a seamless coupling of satellites. The result: everyone in the audience enjoys the same excellent sound experience, regardless of where they are standing in the venue.

Loudspeaker with WaveAhead® technology



Symmetrical horizontal dispersion



Wide dispersion of mid and high frequencies

Conventional loudspeaker



Asymmetrical horizontal dispersion



Wide dispersion of mid frequencies, narrow dispersion of high frequencies

The coaxial arrangement of the WaveAhead® technology solves the interference issues of conventional loudpseakers and allows for a wide and even sound dispersion. With this unique setup you get the best of both worlds, an extra large sound coverage and a very compact design.

16 | CURV® 500 | C

SPECIFICATIONS

MODEL NAME	CURV 500°ES	CURV 500°AVS	CURV 500°PS
TYPE:	Portable Array System Entertainer Set Including Distance Bar & Speaker Cable	Portable Array System AV Set Including Speaker Cables	Portable Array System Power Set Including Distance Bars & Speaker Cables
RATED SYSTEM POWER (RMS):	460 W	380 W	920 W
NUMBER OF ARRAY SATELLITES:	4	2	8
NUMBER OF SMARTLINK® ADAPTERS:	1	2	2
NUMBER OF SUBWOOFERS:	1	1	2
MAX. SPL (CONTINUOUS):	122 dB	116 dB	128 dB
MAX. SPL (PEAK):	128 dB	122 dB	134 dB
SUBWOOFER:	10" bass reflex		
SATELLITE:	MF: 1 x 4" / HF: 3 x 1" with WaveAhead® Technology / 16 ohms		
FREQUENCY RESPONSE:	47 Hz - 20 kHz		
DISPERSION (H X V):	110° horizontal, 10° vertical per satellite		
AMPLIFICATION:	Class D		
	Subwoofer: 300 W / 1200 W		Subwoofer: 300 W / 1200 W, Satellite: 2 x 160 W / 2 x 640 W
	Satellite: 2 x 160 W / 2 x 640 W		Subwoofer Extension: 300 W / 1200 W, 1 x 160 W / 1 x 640 W (Satellite)
PROTECTION:	DSP based multiband-limiter, Short Circuit, Overheating, Over-current		
SUBWOOFER FEATURES:	4 channel mixer, Bluetooth®, 16 DFX Presets, 4 System DSP Presets, threaded M20 Flange, 3 ergonomic handels		
SUBWOOFER CONTROLS:	Input Level (Ch1-4), Hi-Z, Hi/Low EQ (Ch1-2), DFX (Ch1-2), DFX Presets, DSP Presets, Blutetooth Link, Mono/Stereo, Sub Level, Main Level		
SUBWOOFER INDICATORS:	Signal, Limit, Bluetooth®, Power		
SUBWOOFER CONNECTORS:	1x Mic/Hi-Z (XLR/6,3mm Jack Combo), 1x Mic (XLR/6,3mm Jack Combo), 2x Line (XLR/6,3mm Jack Combo), 3,5mm Jack, 2 x Array Satellite Out (Speakon compatible), Line Out (XLR), System Out (5-pin XLR)		
SUBWOOFER MATERIAL:	Plywood		
SUBWOOFER SURFACE:	PA Painting		
ARRAY SATELLITE FEATURES:	WaveAhead® Technology, internal crossover, metal grille, thread for safety rope.		
ARRAY SATELLITE MATERIAL:	Diecast Aluminium		
ARRAY SATELLITE SURFACE:	Powder coating		
SMARTLINK® ADAPTER FEATURES:	dual 16 mm fange, 2x M6 thread for optional wall mount, 4x Thread for optional ceilling mount		
SMARTLINK® ADAPTER CONNECTORS:	1x Speakon compatible, 1x Phoenix		
SMARTLINK® ADAPTER MATERIAL:	Diecast Aluminium		
SMARTLINK® ADAPTER SURFACE:	Powder coating		
SUBWOOFER DIMENSIONS (W X H X D):	325 x 383 x 491 mm		
ARRAY SATELLITE DIMENSIONS (W X H X D):	122 x 122 x 122 mm		
SMARTLINK® ADAPTER DIMENSIONS (W X H X D):	122 x 57 x 122 mm		
SUBWOOFER WEIGHT:	16,5 kg		
ARRAY SATELLITE WEIGHT:	1,7 kg		
SMARTLINK® ADAPTER WEIGHT:	0,6 kg		

MODEL NAME	CURV 500°IAMP	
TYPE:	4-Channel DSP controlled amplifier	
RATED OUTPUT POWER (1 KHZ @ 2 OHM):	4 x 500 W	
RATED OUTPUT POWER (1 KHZ @ 4 OHM):	4 x 300 W	
RATED OUTPUT POWER (1 KHZ @ 8 OHM):	4 x 150 W	
AMPLIFICATION:	Class D	
FREQUENCY RESPONSE:	20 Hz - 20000 Hz	
THD:	< 0,1 %	
PROTECTION CIRCUITS:	Over-current, soft-Start, DC, thermal overload, short circuit	
CONTROLS:	Push encoder	
INDICATORS:	OLED graphic display	
MAXIMUM DELAY / CHANNEL:	48 m	
EQ:	8 x Parametric / Channel	
LINE INPUTS:	4	
LINE INPUT CONNECTORS:	XLR (symmetrical)	
LOUDSPEAKER OUTPUTS:	4	
SPEAKER OUTPUT CONNECTIONS:	Speakon compatible, terminal block (phoenix)	
COOLING:	Temperature-controlled low-noise fan	
OPERATING VOLTAGE:	Switching power supply, 115 V AC / 230 V AC (automatic switchable)	
POWER CONSUMPTION @ FULL LOAD:	1000 W	
DIMENSIONS (W X H X D):	482 X 44 X 350 mm	
WEIGHT:	4,2 kg	

MODEL NAME	CURV 500°ISUB
TYPE:	10" installation subwoofer
PRODUCT NUMBER:	LDCURV500ISUB
PRODUCT TYPE:	Installation subwoofer
TYPE:	Passive
LOW DRIVER DIMENSIONS:	10"
LOAD RATING (RMS):	300 W
FREQUENCY RESPONSE:	47 Hz - 150 Hz
IMPEDANCE:	4 Ohms
LOUDSPEAKER INPUTS:	2 x Speakon compatible , 1 x terminal block (phoenix)
CABINET MATERIAL:	15 mm MDF
CABINET SURFACE:	Texture paint
COLOR:	Black or white
CABINET CONSTRUCTION:	Bassreflex
DIMENSIONS (W X H X D):	610 X 310 X 230 mm
WEIGHT:	14,5 kg
FEATURES:	Low profile ceiling/ wall mounting bracket

SETS & **EXTENSIONS**



CURV 500 ES
Portable Array System
Entertainer Set



CURV 500 PS
Portable Array System
Power Set



CURV 500 AVS W
Portable Array System
A/V Set



CURV 500 AVS
Portable Array System
A/V Set



CURV 500 PES

Power Extension Set
composed of 1 Subwoofer
Extension + 4 Array Satellites
+ SmartLink® Adapter +
Distance Bar + Speaker Cable.



CURV 500 STS
Stereo Set composed of a
SmartLink® Adapter + distance bar
+ Speaker stand base + Cable.



CURV 500 DB
Distance Bar
for CURV 500®
portable Array
System





CURV 500 SE
Subwoofer Extension
for CURV 500® portable
Array System



CURV 500 S2 /W 2 x Array Satellites for CURV 500® portable Array System





CURV 500 SAT BAG
Satellites Transport Bag
for 4 CURV 500® Satellites





CURV 500 SUB PC
Transport Trolley
for CURV 500® Subwoofer

AUDIO VIDEO SETCONFIGURATION GUIDE











POWER SETCONFIGURATION GUIDE





AWARD WINNING DESIGN MADE PORTABLE.









YOUR LOCAL DEALER:



